

Lutz Pump Sets

3 Pump Set „Alkalis“

For thin-bodied alkalis

such as sodium chloride, kalihydrate, ammonia solution, formic acid and acetic acid.

- **Motor MI-4**, 500 W internally ventilated or optionally with
- **Motor MA II 3**, 460 W externally ventilated

Motor MI-4
For individual application.
For aggressive and non-flammable liquids.

Motor MI-4

Density (kg/dm ³)	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1,4	500	87 (50)	19

Motor MA II 3

Density (kg/dm ³)	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1,6	500	78 (45)	16

Max. temperature of medium 50 °C

Specified values are maximum values determined with water at 20°C, measured directly at the pressure joint. Viscosity determined with oil. When using a nozzle the delivery rate is reduced to approximate values (see brackets).



Pump Set Alkalis

with motor MA II 3
externally ventilated



Pump Set Alkalis



with motor MI-4
internally ventilated

with shaft SS

(stainless steel 1.4571)



For emptying drums and containers

			Pump* with MI-4	Pump* with MA II 3	Set with MI-4	Set with MA II 3
	Imm. depth 1000 mm	Order No.	0205-105	0205-125	0205-101	0205-121
	Imm. depth 1200 mm	Order No.	0205-106	0205-126	0205-102	0205-122

Pump Set: **Motor MI-4 or MA II 3**,
pump tube PP 41-L-SL SS polypropylene with stainless steel shaft,
2 m PVC spiral hose 3/4" and hose connections, hose clamps,
nozzle PP, drum adapter PP.

*Motor, pump tube PP, hose connection 3/4"