

More time for the essential things

4 Pump Set „Acids“

For thin-bodied acids

such as hydrochloric acid, battery acid, ferric (III) chloride, phosphoric acid, chromic acid and citric acid.

- **Motor MA II 3**, 460 W externally ventilated or optionally with
- **Motor MI-4**, 500 W internally ventilated

Motor MA II 3

For fuming liquids or corrosive vapours. Powerful, externally ventilated universal motor.

Motor MA II 3

Density (kg/dm ³)	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1,6	500	78 (45)	16

Motor MI-4

Density (kg/dm ³)	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1,4	500	87 (50)	19

Max. temperature of medium 50 °C

Specified values are maximum values determined with water at 20°C, measured directly at the pressure joint. Viscosity determined with oil. When using a nozzle the delivery rate is reduced to approximate values (see brackets).



Pump Set Acids

with motor MI-4
internally ventilated



Pump Set Acids

with motor MA II 3
externally ventilated





Easy fluid measurement optionally with flow meter TR90-PP
Order No.: 0213-032

with shaft HC

(Hastelloy C)



For emptying drums and containers		Pump* with MI-4	Pump* with MA II 3	Set with MI-4	Set with MA II 3
 Imm. depth 1000 mm	Order No.	0205-115	0205-135	0205-111	0205-131
 Imm. depth 1200 mm	Order No.	0205-116	0205-136	0205-112	0205-132

Pump Set: **Motor MI-4 or MA II 3**, **pump tube PP 41-L-SL HC** polypropylene with Hastelloy C shaft, **2 m** PVC spiral hose 3/4" and hose connections, hose clamps, nozzle PP, drum adapter PP.

*Motor, pump tube PP, hose connection 3/4"