

Lutz Pump Sets

1 Pump Set Lutz B2 Vario (Polypropylene)

For thin-bodied fluids

such as battery acid, ammonia solution, photographic developer/-fixer, glycols, phosphoric acid, hydrochloric acid and hydrogen peroxide.

For filling small quantities from hobbocks, canisters and drums.

- **Motor Lutz B2 Vario**,
200 W internally ventilated

Density (kg/dm ³)	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1,3	300	75 (22)	7

Max. temperature of medium 50 °C

Specified values are maximum values determined with water at 20°C, measured directly at the pressure joint. Viscosity determined with oil. When using a nozzle the delivery rate is reduced to approximate values (see brackets).



Pump Set Lutz B2 Vario

for thin-bodied fluids

with shaft HC
(Hastelloy C)

For emptying canisters and drums		Pump Lutz B2 Vario*	Pump Set Lutz B2 Vario
	Immersion depth 500 mm	Order No. 0201-500	0205-020
	Immersion depth 700 mm	Order No. 0201-501	0205-021
	Immersion depth 1000 mm	Order No. 0201-502	0205-022



Pump Set: **Pump Lutz B2 Vario**
polypropylene, 1.5 m PCV spiral hose
3/4", Lutz-nozzle, hose clamps,
wall bracket.

*Pump B2 with hose connection PP 3/4"