

More time for the essential things

2 Pump Set Lutz B2 Vario (Stainless Steel)

For thin-bodied fluids

such as oil-based lubricants, cleaner solvent, plasticizer.

For filling small quantities from hobbocs, canisters and drums.

- **Motor Lutz B2 Vario,**
200 W internally ventilated

Density (kg/dm ³)	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1,3	300	68 (22)	6,5

Max. temperature of medium 90 °C

Specified values are maximum values determined with water at 20°C, measured directly at the pressure joint. Viscosity determined with oil. When using a nozzle the delivery rate is reduced to approximate values (see brackets).



Pump Set Lutz B2 Vario

for thin-bodied fluids

with shaft SS

(stainless steel 1.4571)

For emptying canisters and drums

Pump Lutz B2 Vario* Pump Set Lutz B2 Vario

	Immersion depth	500 mm	Order No.	0201-510	0205-030
	Immersion depth	700 mm	Order No.	0201-511	0205-031
	Immersion depth	1000 mm	Order No.	0201-512	0205-032



Pump Set: **Pump Lutz B2 Vario** stainless steel, 1.5 m PCV spiral hose 3/4", Lutz-nozzle, hose clamps, wall bracket.

*Pump B2 with hose connection SS 3/4"