

# More time for the essential things

## 6 Pump Set „Mineral Oil Products“

### For light viscous mineral oil products

such as Diesel, fuel oil, hydraulic oil, machinery oil and motor oil.

- **Motor MI-4**, 500 W internally ventilated or optionally with
- **Compressed air motor MD-1**, 400 W / 6 bar with stop valve and nipple

**Motor MI-4**  
Universal motor for individual application. For aggressive and non-flammable liquids. Strong when handling mineral oil products.

#### Motor MI-4

Density (kg/dm <sup>3</sup> )	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1,4	500	87 (50)	19

#### Motor MD-1

Density (kg/dm <sup>3</sup> )	Viscosity (mPas)	Delivery rate (l/min.)	Delivery head (m wc)
1,8	850	90 (65)	20

Max. temperature of medium 100 °C

Specified values are maximum values determined with water at 20°C, measured directly at the pressure joint. Viscosity determined with oil. When using a nozzle the delivery rate is reduced to approximate values (see brackets).

### Pump Set Mineral Oil Products

with motor MI-4 internally ventilated or MD 1

#### Motor MD-1

The compact compressed air motor is powerful and reliable.



#### For emptying drums and containers

		Pump* with MI-4	Pump* with MD-1	Set with MI-4	Set with MD-1
	Imm. depth 1000 mm	Order No. 0205-305	0205-315	0205-301	0205-311
	Imm. depth 1200 mm	Order No. 0205-306	0205-316	0205-302	0205-312

Pump Set: **Motor MI-4 or MD-1**, pump tube **Alu 41-L-SL** aluminium, 2 m PVC spiral hose 1" and hose connections, hose clamps, nozzle Alu, drum adapter PP.

\*Motor, pump tube alu, hose connection 1"

(For high viscous oils suitable Eccentric Screw Pumps are available, see separate leaflet)